

## Polyurethane Product Sheet

Extremely High Mechanical Properties  
 High Protective Abrasion/Tear Resistance  
 Good Resistance to Ozone/Natural Aging

Resistant to Aliphatic Solvents

High Temperature Limit: 160°F

Shelf Life: 3 Years

Standard Length: 32" +/- 1 inch

\*Any Length Requirements Other than Standard is Custom

\*Call for Pricing

NAICS CODE: 339113

<b>Polyurethane Material</b>					
<b>Long Gloves</b>					
Part Number	Port Size	Thickness	Length	Hand Size	Hand Style
6U1532-X	6" (150mm)	15 mil (0.4mm)	32" (812 mm)	8.5, 9.75, 10.5	A or L/R
7U1532-X	7" (175mm)	15 mil (0.4mm)		9.75, U	A
8U1532-X	8" (200mm)	15 mil (0.4mm)		8.5, 9.75, 10.5, U	A or L/R
10U1532-X	10" (250mm)	15 mil (0.4mm)		8.5, 9.75, 10.5	A
12U1532-X	12" (305mm)	15 mil (0.4mm)		9.75	A
<b>Short Isolators</b>					
U15-X		15 mil (0.4mm)	13" (330 mm)	5, 6, 7, 8, 9, 10	A