

Polyurethane/CSM Product Sheet

Highest Performance with In Situ Leak Detectors
 High Mechanical Properties
 High Protective Abrasion/Tear Resistance
 Good Resistance to UV Rays/Ozone/Natural Aging
 Resistant to Reducing Acids, Diluted Acids, Alkalis, and Salts
 High Temperature Limit: 160°F
 Shelf Life: 3 Years
 Standard Length: 32" +/- 1 inch
 *Any Length Requirements Other than Standard is Custom
 *Call for Pricing

NAICS CODE: 339113

Polyurethane/CSM Material					
Long Gloves					
Part Number	Port Size	Thickness	Length	Hand Size	Hand Style
6UY2032-X	6" (150mm)	20 mil (0.5mm)	32" (812 mm)	8.5, 9.75, 10.5	A or L/R
7UY2032-X	7" (175mm)	20 mil (0.5mm)		9.75, U	A
8UY2032-X	8" (200mm)	20 mil (0.5mm)		8.5, 9.75, 10.5, U	A or L/R
10UY2032-X	10" (250mm)	20 mil (0.5mm)		8.5, 9.75, 10.5	A
12UY2032-X	12" (305mm)	20 mil (0.5mm)		9.75	A
Short Isolators					
UY20-X		20 mil (0.5mm)	13" (330mm)	5, 6, 7, 8, 9, 10	A
YUY20-X		20 mil (0.5mm)		5, 6, 7, 8, 9, 11	A
YUY24-X		24 mil (0.6mm)		5, 6, 7, 8, 9, 12	A